

# Drahtgewickelte Rohrwiderstände Culatti AG

## Lieferangebot Typ FS



www.culatti.ch  
info@culatti.ch

Grösse	I	II	III	IV	V	VI	VII	VIII	IX	
Leistung	80 W	120 W	200 W	300 W	500 W	700 W	1000 W	1200 W	1500 W	
ø x Länge in mm	30x120	30x150	30x200	45x200	45x300	45x400	60x400	60x500	60x600	
Nr.	Belastung max.									
	Amp.	Ω	Ω	Ω	Ω	Ω	Ω	Ω	Ω	Ω
1	0.15	3500	5200	8000	12500	21000	30000	40000	51000	62500
2	0.175	2600	4000	6000	9200	15800	22000	30000	38500	47000
3	0.2	1800	2650	4100	6300	10600	15000	20000	26000	32000
4	0.25	1300	1900	2900	4500	7550	11000	15000	18500	23000
5	0.3	900	1350	2000	3200	5400	7600	10000	13000	16500
6	0.35	650	1000	1500	2300	3900	5500	7500	9500	11800
7	0.4	450	660	1000	1550	2650	3800	5000	6500	7800
8	0.5	330	500	750	1150	2000	2800	3700	4800	6000
9	0.6	220	330	500	800	1350	1900	2500	3250	4000
10	0.7	160	230	360	550	950	1350	1800	2300	2900
11	0.9	120	175	270	400	700	1000	1350	1700	2100
12	1	80	120	190	290	490	690	920	1200	1460
13	1.2	55	80	125	190	325	460	610	800	1000
14	1.4	40	58	90	135	230	330	430	560	690
15	1.7	28	40	65	100	170	240	320	410	500
16	2	21	30	50	75	125	180	240	310	380
17	2.5	14	20	33	50	90	125	165	215	260
18	2.8	10	15	23	35	60	90	115	150	185
19	3.4	7	10	15	24	40	60	75	100	125
20	4	5	7	11	16	28	40	55	70	85
21	4.8	3.5	5.2	8	12	20	28	40	50	65
22	5.5	2.6	4	6	9.2	15	21	30	38	46
23	6.5	1.7	2.6	4	6.2	10	15	20	25	31
24	8	1.25	2	2.9	4.5	7.5	11	14	18	22
25	9	1	1.3	2.1	3.2	5.5	8	11	13.5	16.5
26	11	0.65	1	1.5	2.2	3.8	5.5	7.5	9.5	11.5
27	13.5	0.45	0.66	1	1.5	2.6	3.7	5	6.4	8
28	16	0.35	0.5	0.75	1.1	1.9	2.7	3.7	4.8	5.8
29	19	0.22	0.33	0.5	0.75	1.3	1.9	2.5	3.2	4

\*Spezielle Widerstandswerte auf Anfrage

Die Rohrwiderstände sind mit folgenden Halterungen erhältlich: FSK für Kopfübermontage, FBK für normale Montage, FR als Schiebewiderstand, F mit Abdeckung, FBK Widerstandskombinationen oder nach Kundenwunsch

